

# **AVOCOR E50** SERIES DATASHEET

55" | 65" | 75" | 86"



### **OVERVIEW**

The Avocor E50 Series sets a new standard in interactive collaboration displays. Ideal for education, corporate, and government environments, the E50 incorporates stunning 4K resolution, intuitive screen sharing functions, and user-friendly connectivity with advanced IR touch control.

The E50 Series is built to support next-generation hybrid workflows and comes pre-loaded with leading screen sharing and digital signage apps from DisplayNote Montage and Rise Vision.

The E50 enhances user engagement through responsive touch capabilities with superior glass technology, providing a smooth and accurate writing experience at low latency. Users can effortlessly switch between stylus, finger, or palm, ensuring a fluid and natural collaborative environment in real-time.

For instant Bring-Your-Own-Meeting (BYOM) and hassle-free presentations, the E50 Series includes multiple front facing guest connectivity options: USB-A, USB-B, Type-C, and HDMI, along with Avocor's UiQ touch-enabled interface for easy access and control. A front-facing presence sensor ensures minimal power consumption when not in use.

## **SOLUTION**

#### Highlights



Avocor UiQ - smart touch enabled dynamic user interface.



FUSE - cloud-based display & software management platform for IT Managers.



Superior glass technology provides an extremely accurate writing experience.



Stunning 4K resolution for crystal-clear visuals.

DisplayNote Montage

Featuring Montage for seamless wireless sharing and Rise Vision for dynamic digital signage, transforms idle displays into hubs of interactive team collaboration



#### **SPECIFICATIONS**

DISPLAY	AVE-5550	AVE-6550	AVE-7550	AVE-8650
Size	55	65	75	86
Backlight	Direct-lit LED			
Aspect Ratio		16		
Resolution	3840 x 2160 @ 60Hz			
Response Time	8 ms			
Brightness	400 (cd/m2)			
Contrast Ratio	1200:1			
Viewing Angle	178° / 178°			
Supported Colors	10 Bit 1.07 Billion Color			
Display Orientation	Landscape			
TOUCH SYSTEM				
nterface	1 x USB-C, 4 x USB-B 3.0			
Touch	Up to 40 Point IR Touch - supports 1 x fine tip stylus			
Glass	Zero parallax, zero-bond, anti-glare, anti-fingerprint glass			
Supported operating system	Windows up to 11; Mac OSX*; Linux*; Chrome			
CPU				
Chipset	Amlogic 311D2			
CPU	Cortex A73*4 + A53*4			
GPU	MaliG52 MP8			
RAM/ROM	4/32GB			
Android version	13			
CONNECTIVITY				
Front Inputs/Guest Inputs	1 x Type-C (65W PD), 1 x HDMI 2.0, 1 x USB-B 3.0 touch, 2 x USB-A 3.0 Hub			
Side Inputs	2 x HDMI 2.0, 1 x DisplayPort 1.2, 1 x Type-C (15W PD), HDCP 2.2, 3 x USB-B 3.0 Touch, 2 x USB-A 3.0 Hub, 1 x USB-A Service Port, 1 x HDMI Out (Support 4K@60Hz, 1920x1080@60Hz)			
udio	1 x 3.5mm audio out, 1 x optical (SPDIF)			
Control	1 x RS-232, 1 x LAN Ethernet (RJ-45) in, 1 x LAN Ethernet (RJ-45) out			
OPS Slot	Yes			
Vi-Fi	Yes			
AUDIO				
Built-in Speakers	2 x 15W - forward facing			
Microphone Array	No			
Camera	No			
Presence Sensor	Yes (except 55")			
DISPLAY & REMOTE FUNCTIO	NS .			
Auto-Source-Detection	Yes			
Source Preview	Yes			
PHYSICAL SPECIFICATIONS				
Product dimensions	1289.5 x 92.6 x 791.6mm 50.76 x 3.64 x 31.6 in	1482.1 x 87.7 x 897.4mm 58.3 x 3.45 x 35.33 in	1716.5 x 86.9 x 1031.8mm 67.5 x 3.42 x 40.62 in	1961.8 x 87.7 x 1169.9mn 77.2 x 3.45 x 46.05 in
Shipping dimensions	1420 x 220 x 870mm 55.9 x 8.66 x 34.2 in	1660 x 220 x 1010mm 65.3 x 8.66 x 39.7 in	1900 x 225 x 1125mm 74.8 x 8.8 x 44.2 in	2160 x 225 x 1310mm 85 x 8.8 x 51.5 in
Veight	Net: 29 kgs   64 lbs Gross: 35 kgs   77 lbs	Net: 38 kgs   84 lbs Gross: 46 kgs   101 lbs	Net: 52.2 kgs   115 lbs Gross: 61.5 kgs   136 lbs	Net: 65.5 kgs   144 lbs Gross: 77 kgs   170 lbs
Vall mount (VESA)	400 x 400mm Included	800 x 400mm Included	800 x 400mm Included	800 x 600mm Included
Handles		2		
PC Mount	100 x 100 mm			
POWER				
Power Supply	AC100-240V (worldwide), 50/60Hz			
Max Power Consumption	210W (w/o OPS)	380W (w/o OPS)	380W (w/o OPS)	460W (w/o OPS)
itandby		≤O.	5W	
NVIRONMENTAL				
Operating temperature	0°C ~ 40°C			
Storage temperature	-20°C ~ 60°C			
Humidity	20% ~ 85%			
WHAT COMES IN THE BOX	4.0			ELL 4 - 110 A - 4110
		batteries, 2 x 3mm fine-tip passive toucl 3.0 cable (3m   118.1 in), 1 x HDMI cable		
WARRANTY				
		Terms and conditions vary v	un region, please click here	



Terms and conditions vary via region, please  $\underline{\text{click here}}$ 





Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE.

\* Please note up to 40 point touch in PC mode with Windows up to 11. Mac OSX and Linux only supports single touch.

\*\*DisplayNote Launcher requires a Windows OPS PC or attached Windows PC. Contact Avocor Support for details.

Version date: 10/03/2025